This SDS version supersedes all previous MSDS for the specified product.



Product: AC823 Issue Date: 2023 JAN Issued by: **PRS** Version: 1.70 1 of 9 Page:

## HAZARDOUS CHEMICAL, DANGEROUS GOODS

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: ISOPROPANOL

**Product Code Synonyms** ISOPROPANOL (IPA) 5L AC823-5 AC823-20 ISOPROPANOL (IPA) 20L ISOPROPANOL (IPA) 200L AC823-200

#### Recommended use:

Isopropyl Alcohol is a bacterial grade disinfectant suitable for general purpose disinfection and hospital equipment not likely to come into contact with broken skin. Don't use in therapeutic devices. Use as per technical advice specific to Industry only.

#### **Product AS SOLD**

Product AS SOLD is classified as hazardous according to GHS and/or Safe Work Australia because of risk to EYES. Contact with EYES is not considered as being applicable to normal use of the product. Avoid direct sprays or contact with EYES as it can cause serious EYE IRRITATION. Avoid inhalation of vapour as it May cause RESPIRATORY IRRITATION. Avoid contact with ignition sources as it can cause FIRE.

Supplier: Able Westchem ABN: 009 353 182 Street Address: 273 Collier Road

Bayswater, WA 6053

Australia

Telephone: +61 8 9471 9111 Facsimile: +61 8 9272 6740

Emergency Telephone number: +61 8 9471 9111 (8.00am-4.30pm: Mon-Fri, AWST)

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.





### Signal Word

Danger

#### **Hazard Classifications**

Flammable Liquids - Category 2 Serious Eye Damage/Irritation - Category 2A

Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 2 of 9

#### **Hazard Statements**

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

#### **Prevention Precautionary Statements**

Tevention Frece	autionally Statements
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator.

## **Response Precautionary Statements**

P101	If medical advice is needed, have product container or label at hand

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use (insert appropriate media) for extinction.

### **Storage Precautionary Statements**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule: Not Applicable

#### **DANGEROUS GOOD CLASSIFICATION**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY CAS NO PROPORTION

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 3 of 9

Isopropyl alcohol 67-63-0 99 – 100 % (w/w)

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

Hazchem Code: •2YE

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Firefighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapour. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WEST CHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 4 of 9

and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal.

Dangerous Goods - Initial Emergency Response Guide No: 16

### 7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Isopropyl alcohol	400	983	500	1230	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 5 of 9

### Personal Protection Equipment:

### **Special Note:**

Personal Protective Equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

The selection of PPE is dependent on a full risk assessment. The risk assessment should consider the work situation, physical form of chemical, handling method and volume, environmental factors and area of application.

If the outcome of risk assessment is considerably low, still manufacturer recommends to use minimum PPE stipulated by the chemical industry practices. Ex: Face shield, Apron, Safety Shoes, Impervious Gloves and Suitable Protective clothes.

RUBBER BOOTS, OVERALLS, GLOVES, APRON, FACE SHIELD, RESPIRATOR.













If the handling volume is large: Wear suitable protective clothing covers unprotected exposed skin area with an Overall chemical resistant Apron, Face shield and suitable respirator must be worn at all times to avoid any injuries. If inhalation or spill risk exists, also if engineering controls are not effective in controlling any airborne contaminants, wear suitable mist respirator meeting the requirements of AS/NZS 1716.

Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from natural rubber, nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour. Ensure that eyewash stations and safety showers are close to the workstation location.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Base Units:LitresForm:Clear LiquidColour:Colourless

Solubility in water: Miscible with water

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 6 of 9

### 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

#### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin may result in irritation.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

#### **Acute toxicity**

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >20 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as not corrosive or irritating to skin.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

**Aspiration hazard:** This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

### **Chronic Toxicity**

Mutagenicity: This material has been classified as non-hazardous.

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 7 of 9

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

#### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

Eco toxicity: No information available.

Persistence and degradability: No information available.

Bio accumulative potential: No information available.

**Mobility:** No information available.

### 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible, material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1219
Dangerous Goods Class: 3
Packing Group: II
Hazchem Code: •2YE
Emergency Response Guide No: 16

Proper Shipping Name: ISOPROPYL ALCOHOL

NO UNAUTHORISED COPIES PERMITTED - DISREGARD SDS WITHOUT OFFICIAL ABLE WESTCHEM LETTERHEAD





This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 8 of 9

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

#### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No: 1219
Dangerous Goods Class: 3
Packing Group: ||

Proper Shipping Name: ISOPROPYL ALCOHOL

#### **AIR TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1219
Dangerous Goods Class: 3
Packing Group: ||

Proper Shipping Name: ISOPROPYL ALCOHOL

## 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material/constituent(s) is covered by the following requirements:

 All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).







This SDS version supersedes all previous MSDS for the specified product.



 Product:
 AC823

 Issue Date:
 2023 JAN

 Issued by:
 PRS

 Version:
 1.70

 Page:
 9 of 9

### 16. OTHER INFORMATION

Reasons for issue: Periodic review and reissue of SDS

Issue date: 13/01/2023 Version: 1.70 Able Rating: Red

### DISCLAIMER:

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. This product was classified according to Globally Harmonised System of Classification and Labelling of Chemicals (GHS) Revision Version 07.

Able Westchem MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Able Westchem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Able Westchem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Able Westchem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. For this reason, Able Westchem always recommends a user perform a test patch or trial in small scale or in an inconspicuous area prior to full application to limit possible damage. Testing before beginning any project is also the best way to ensure product effectiveness.

Able Westchem provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Able Westchem makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Able Westchem.



