# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

#### **SECTION 1. IDENTIFICATION**

Product name : BENOX®L-40LV

Manufacturer or supplier's details

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street

Elyria OH 44035 USA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300

CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person

responsible for the SDS

: cs-initiators.nafta@united-in.com

Recommended use of the chemical and restrictions on use

Recommended use : Curing chemical

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Organic peroxides : Type E

Eye irritation : Category 2B

Skin sensitization : Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

**GHS** label elements

Hazard pictograms







Signal Word : Warning

Hazard Statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H320 Causes eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.

P234 Keep only in original container.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

# Storage:

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding 30 °C/ 86 °F.

Keep cool.

P420 Store away from other materials.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Organic Peroxide

Liquid mixture

# Components

| Chemical name      | CAS-No.  | Concentration (% w/w) |  |
|--------------------|----------|-----------------------|--|
| Dibenzoyl peroxide | 94-36-0  | >= 35 - < 40          |  |
| Zinc stearate      | 557-05-1 | >= 1 - < 5            |  |

# BENOX®L-40LV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/08/2019

 3.0
 12/04/2019
 600000000152
 Date of first issue: 06/27/2017

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended. Call a physician immediately.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician. If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water. If on clothes, remove clothes. If symptoms persist, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Call a physician immediately.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-

# BENOX®L-40LV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/08/2019

 3.0
 12/04/2019
 600000000152
 Date of first issue: 06/27/2017

accelerating decomposition reaction with release of flammable

vapors which may auto-ignite.

The product burns violently.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

The product will float on water and can be reignited on surface

water.

Cool closed containers exposed to fire with water spray.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire.

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition.

Follow safe handling advice and personal protective

equipment recommendations.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contact with incompatible substances can cause

decomposition at or below SADT.

Clear spills immediately.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

To clean the floor and all objects contaminated by this

material, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on protection against

fire and explosion

Keep away from heat and sources of ignition.

Use only explosion-proof equipment. Keep away from combustible material.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the

application area.

Wash thoroughly after handling. For personal protection see section 8.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Electrical installations / working materials must comply with

the technological safety standards.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in original container.

Keep containers tightly closed in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem: :

perature

0 - 30 °C

32 - 86 °F

Further information on stor- : No decomposition if stored normally.

# **BENOX<sup>®</sup>L-40LV**



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

age stability

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Ingredients with workplace control parameters

| Components         | CAS-No.  | Value type     | Control parame-    | Basis     |
|--------------------|----------|----------------|--------------------|-----------|
|                    |          | (Form of       | ters / Permissible |           |
|                    |          | exposure)      | concentration      |           |
| Dibenzoyl peroxide | 94-36-0  | TWA            | 5 mg/m3            | ACGIH     |
|                    |          | TWA            | 5 mg/m3            | NIOSH REL |
|                    |          | TWA            | 5 mg/m3            | OSHA Z-1  |
|                    |          | TWA            | 5 mg/m3            | OSHA P0   |
| Zinc stearate      | 557-05-1 | TWA (Res-      | 5 mg/m3            | NIOSH REL |
|                    |          | pirable)       |                    |           |
|                    |          | TWA (total)    | 10 mg/m3           | NIOSH REL |
|                    |          | TWA (total     | 15 mg/m3           | OSHA Z-1  |
|                    |          | dust)          |                    |           |
|                    |          | TWA (respir-   | 5 mg/m3            | OSHA Z-1  |
|                    |          | able fraction) |                    |           |
|                    |          | TWA (Total     | 10 mg/m3           | OSHA P0   |
|                    |          | dust)          |                    |           |
|                    |          | TWA (respir-   | 5 mg/m3            | OSHA P0   |
|                    |          | able dust      |                    |           |
|                    |          | fraction)      |                    |           |
|                    |          | TWA (Inhal-    | 10 mg/m3           | ACGIH     |
|                    |          | able fraction) |                    |           |
|                    |          | TWA (Res-      | 3 mg/m3            | ACGIH     |
|                    |          | pirable frac-  |                    |           |
|                    |          | tion)          |                    |           |

**Engineering measures** : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous

substance and specific to place of work.

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove Wash hands before breaks and at the

end of workday.

# **BENOX®L-40LV**



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Eye protection : Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face

protection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close

to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Hygiene measures : Keep away from food and drink.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Emulsion

Color : white

Odor : characteristic

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : Decomposition: Decomposes below the boiling point.

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : does not ignite

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : Not applicable

Density : 1.2 g/cm3 (25 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

# **BENOX®L-40LV**



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Self-Accelerating decomposi-

tion temperature (SADT)

50 °C

SADT-Self Accelerating Decomposition Temperature. Lowest

temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Viscosity

Viscosity, dynamic : 1 mPa.s

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable under recommended storage conditions.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause

decomposition at or below SADT.

Heat, flames and sparks. Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

Hazardous decomposition

products

Irritant, caustic, flammable, noxious/toxic gases and vapours

can develop in the case of fire and decomposition

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

# **Components:**

Dibenzoyl peroxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 24.3 mg/l

Exposure time: 4 h
Test atmosphere: vapor

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : Remarks: No data available

Zinc stearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 200 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : May cause skin irritation in susceptible persons.

### **Components:**

Dibenzoyl peroxide:

Species : Rabbit

Result : No skin irritation

Zinc stearate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

# Serious eye damage/eye irritation

Causes eye irritation.

**Product:** 

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

## **Components:**

Dibenzoyl peroxide:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

# **BENOX®L-40LV**



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Zinc stearate:

Species : Rabbit

Result : No eye irritation Method : Draize Test

## Respiratory or skin sensitization

# Skin sensitization

May cause an allergic skin reaction.

# Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

## **Components:**

Dibenzoyl peroxide:

Routes of exposure : Skin contact Species : Mouse

Method : Local lymph node assay (LLNA)

Result : May cause sensitization by skin contact.

Zinc stearate:

Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

Remarks : Information given is based on data obtained from similar sub-

stances.

# Germ cell mutagenicity

Not classified based on available information.

### Components:

Dibenzoyl peroxide:

Genotoxicity in vitro : Result: negative

Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: negative

Remarks: In vivo tests did not show mutagenic effects

Zinc stearate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Genotoxicity in vivo : Test Type: Chromosomal aberration

Species: Rat

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Result: Equivocal

# Carcinogenicity

Not classified based on available information.

# **Components:**

# Dibenzoyl peroxide:

Remarks : Not classified due to data which are conclusive although insuf-

ficient for classification.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

# Reproductive toxicity

Not classified based on available information.

# **Components:**

# Dibenzoyl peroxide:

Effects on fertility : Species: Rat, male

**Application Route: Oral** 

General Toxicity Parent: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 422

Species: Rat, female Application Route: Oral

General Toxicity Parent: NOAEL: 500 mg/kg body weight

Method: OECD Test Guideline 422

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

# Zinc stearate:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity F1: NOAEL: 7.5 mg/kg body weight

Method: OECD Test Guideline 416

Remarks: Based on data from similar materials

Effects on fetal development : Species: Mouse

Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: 30 mg/kg body weight

Teratogenicity: NOAEL: 30 mg/kg body weight Remarks: Based on data from similar materials

# BENOX®L-40LV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/08/2019

 3.0
 12/04/2019
 600000000152
 Date of first issue: 06/27/2017

# STOT-single exposure

Not classified based on available information.

# **Components:**

# Dibenzoyl peroxide:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

# STOT-repeated exposure

Not classified based on available information.

# **Components:**

# Dibenzoyl peroxide:

Routes of exposure : Ingestion

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

# Repeated dose toxicity

## **Components:**

# Zinc stearate:

Species : Mouse NOAEL : 458 mg/kg

Application Route : Oral

Method : OECD Test Guideline 408

## **Aspiration toxicity**

Not classified based on available information.

## **Components:**

# Dibenzoyl peroxide:

No aspiration toxicity classification

# **Further information**

### **Product:**

Remarks : No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

# **Product:**

# **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

# **BENOX®L-40LV**



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

**Components:** 

Dibenzoyl peroxide:

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.06 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.06

mg/I

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

. .

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 0.001 mg/l

Exposure time: 21 d

Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to microorganisms : EC50 (Bacteria): 35 mg/l

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Zinc stearate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 1,000 mg/l

Exposure time: 0.5 h Method: DIN 38 412 Part 8

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

# Persistence and degradability

**Components:** 

Dibenzoyl peroxide:

Biodegradability : Result: Inherently biodegradable.

Zinc stearate:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

**Bioaccumulative potential** 

**Components:** 

Dibenzoyl peroxide:

Partition coefficient: n-

octanol/water

log Pow: 3.2 (20 °C / 20 °C)

Zinc stearate:

Partition coefficient: n-

octanol/water

Remarks: No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with local regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

**UNRTDG** 

UN number : UN 3107

Proper shipping name : ORGANIC PEROXIDE TYPE E, LIQUID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

**IATA-DGR** 

UN/ID No. : UN 3107

Proper shipping name : Organic peroxide type E, liquid

(Dibenzoyl peroxide)

Class : 5.2

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction (passen: 570

ger aircraft)

**IMDG-Code** 

UN number : UN 3107

Proper shipping name : ORGANIC PEROXIDE TYPE E, LIQUID

(DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

UN/ID/NA number : UN 3107

Proper shipping name : Organic peroxide type E, liquid

(Dibenzoyl peroxide, <=42%)

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 145 Marine pollutant : yes

Special precautions for user

# BENOX®L-40LV



Version Revision Date: SDS Number: Date of last issue: 03/08/2019 3.0 12/04/2019 600000000152 Date of first issue: 06/27/2017

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

# **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Organic peroxides

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Dibenzoyl perox- 94-36-0

ide

Zinc stearate 557-05-1

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Zinc stearate 557-05-1

## California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

# The ingredients of this product are reported in the following inventories:

DSL (CA) : All components of this product are on the Canadian DSL

# BENOX®L-40LV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/08/2019

 3.0
 12/04/2019
 600000000152
 Date of first issue: 06/27/2017

AICS (AU) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : On TSCA Inventory

### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA, OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

# BENOX®L-40LV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/08/2019

 3.0
 12/04/2019
 600000000152
 Date of first issue: 06/27/2017

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 12/04/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8