

Single Sheave Snatch Block with Hook

Art.no.	Model	Description	Weight (kgs)
475092012QR3	SB2S3BH	WLL 2 MT, Sheave OD 3" / 80 mm, suits 8 - 10 mm wire rope	2.3
474655016QR3	SB4S4BH	WLL 4 MT, Sheave OD 4" / 100 mm, suits 10 - 13 mm wire rope	6.8
474601024QR3	SB8S8BH	WLL 8 MT, Sheave OD 8" / 200 mm, suits 16-20 mm wire rope	15.9
474577028QR3	SB12S8BH	WLL 12 MT, Sheave OD 8" / 200 mm, suits 20 - 22 mm wire rope	25.9
475131036QR3	SB20S10BH	WLL 20 MT, Sheave OD 10" / 250 mm, suits 26 - 30 mm wire rope	43.1



Manhandler Snatch Block

Gunnebo Johnson's Manhandler Snatch Blocks (MHSB) are suitable for personnel hoisting when properly incorporated into a compliant personnel hoist system and maintained in good working order.

See the *Manhandler Warnings and Use Limitations Brochure* available from Gunnebo Johnson Corp. and your distributor.

- Standard painted finish
- For lifting personnel
- Sealed roller bearings
- Interlocking internal design
- R-pins retainers
- Secondary tether attachment points

Art. no	Model	Wire rope mm	Sheave diameter mm	WLL kgs	Weight kgs
687431014	MHSB1S8RS	10 - 11	200	680	22



Galvanized Derrick Block

- 4 - 12 tonnes WLL
- Standard galvanized finish
- Handling slots in the body
- Large knock-off handles
- Interlocking internal design
- For lifting materials
- R-Pin retainers

Art. no	Model	Wire rope mm	Sheave diameter mm	WLL tonnes	Weight kgs
687710016	MHSB4S8TS	10 - 13	200	4	15
687334018	MHSB12S10TS	13 - 14	250	12	37.6



Swivel, jaw-jaw

Art.no.	Model	Description	Weight (kgs)
670665	3 JJM	3 T Thrust bearing swivels, jaw-jaw	3.6
670667	7 JJ	7 T Thrust bearing swivels, jaw-jaw	9.9
670668	12 JJ	12 T Thrust bearing swivels, jaw-jaw	18.9
670379	19 JJ	19 T Thrust bearing swivels, jaw-jaw	21.6

